

Imagen



Standard Equipment	GBT-400
Length(mm)	3220(2100,the low bar be retracted or detached)
Width(mm)	1620
Height(mm)	2250
Height(Mast be extended fully,m)	9
Weight(Dry,kg)	1250
Engine model	GB POWER 380
Frequency(Hz)	60
Speed(rpm)	1800
Continued Power(kVA)	9
Number of Cylinders	3
Diesel Engine Characters	4-cycle,In line,Watercooled Diesel
Combustion Type	Direct Injection
Engine Aspiration	Naturally aspirated
Emission Level	
Alternator	Stamford or Loerysomer Brushless & Single
Rating Voltage(V)	230
Alternator Insulation	Class H
Fuel Tank Type	Bunded Tank
Type of Lights	Metal Halide Floodlight/Rectangle(E40/E39,GEWISS)
Number & Power of Lights	4*1000W
Mast Extension	Hydraulic operation or Manual Type
Mast Erection Time	<30 Seconds
Mast Rotation	330° Manual Operation
Light Bar Tilt	90° Electrically
Control System	Deepsea 3110
Stablizing Legs	Manually
Trailer Suspension&braking System	Leaf spring axle with drum brake
Hitch & tow bar	Ball or O ring & stable hitch in heigh
Tire Rim Size	14"
Output Sockets	1 PCS(230V,10A)
Acoustic Pressure	65 dB(A) AT 7 meter away
Max.load quantity in a 40' container(sets)	7